

INSTALLATION EXAMPLE DID 604

[view](#)

Application range

Type

Installation example

TYPE DID 604

Active chilled beam with four-way air discharge, vertical heat exchanger and condensate drip tray, for grid ceilings with grid size 600 or 625

Active chilled beam for heating and cooling, with 2-pipe or 4-pipe heat exchanger, for integration with various ceiling systems. The condensate drip tray is useful if the temperature temporarily falls below the dew point.

- Preferably for room heights up to 4.00 m
- High heating and cooling capacity with a low conditioned primary air volume flow rate and low sound power level
- High comfort levels due to low airflow velocity in the occupied zone
- Three nozzle variants to optimise induction based on demand
- Removable induced air grille, fixed with magnets

Optional equipment and accessories

- Control system
- Adjustable air control blades for air direction control
- Heat exchanger powder-coated black
- Powder coating in many different colours, e.g. RAL CLASSIC

For further product information please [click here](#)

TROX UK Ltd



Caxton Way,
Thetford, Norfolk, IP24 3SQ, UK
Tel: +44 (0) 1842 754545
Fax: +44 (0) 1842 763051

General Enquiries –
info@troxuk.co.uk
Sales & Customer Services –
sales@troxuk.co.uk
Accounts –
accounts@troxuk.co.uk

Online-Services

- > [TROX Academy](#)

- > [Your contact partner](#)

- > [Our Office London](#)

- > [Our Office Thetford](#)

Service-Hotlines

Sales:
+44 (0)1842 754545
[Contact](#)

Service:
+44 (0)1842 754545
[Contact](#)

Technical service
+44 (0)1842 754545
[Contact](#)