



## TYPE LFP

PRIMARYLY USED FOR SUPPLY AIR APPLICATIONS BUT CAN BE USED FOR EXTRACT WHEN MATCHING DIFFUSERS ARE REQUIRED. TOP ENTRY PRIMARY AIR CONNECTION.

The Laminar Flow Panel type, LFP, has been developed for specialist applications where the mixing of supply air with room air must be avoided.

- Recommended supply air temperature difference -5 to -10K
- The diffuser provides a stable, low turbulence vertical discharge into the occupied zone.
- This makes the TROX Type LFP ideal for clean rooms, laboratories, operating theatres, broadcasting studios and computer rooms.

### Optional equipment and accessories

- All visible surfaces finished in polyester powder coat to RAL9010:20% gloss as standard. Other paint finishes are available on request.

### TROX UK Ltd

---

□

Caxton Way,  
Thetford, Norfolk, IP24 3SQ, UK  
Tel: +44 (0) 1842 754545  
Fax: +44 (0) 1842 763051

General Enquiries –  
[info@troxuk.co.uk](mailto:info@troxuk.co.uk)  
Sales & Customer Services – [sales@troxuk.co.uk](mailto:sales@troxuk.co.uk)  
Accounts –  
[accounts@troxuk.co.uk](mailto:accounts@troxuk.co.uk)

### Online-Services

---

- > [TROX Academy](#)
- > [Your contact partner](#)
- > [Our Office London](#)
- > [Our Office Thetford](#)

### Service-Hotlines

---

Sales:  
+44 (0)1842 754545  
[Contact](#)

Service:  
+44 (0)1842 754545  
[Contact](#)

Technical service  
+44 (0)1842 754545  
[Contact](#)

### TROX SOCIAL MEDIA

---