

## Type TFC



### FOR CRITICAL AIR CLEANLINESS AND CRITICAL HYGIENE REQUIREMENTS, SUITABLE FOR CEILING INSTALLATION

Ceiling mounted particulate filters as final filter stage with Mini Pleat filter panels for the separation of suspended particles. Used in medicine, biology, pharmaceuticals, and sensitive technical areas.

- Easy, time-saving and secure filter change, can be completed by one person due to special press-in frame
- Robust, welded construction
- Compact construction, suitable for low ceilings, integration with all clean room ceiling systems of various manufacturers
- Various diffusers to ideally meet individual requirements
- Horizontal (circular, rectangular) or vertical (circular) connection
- Choice of air-tight shut-off damper or volume flow limiter for horizontal connection
- Equipment for differential pressure measurement, sealing integrity testing, and particle sampling for measurement
- For air cleanliness classes 5 to 8 according to ISO 14644-1
- Meets the hygiene requirements of VDI 6022



### Application

- Particulate filter air terminal device type TFC for ceiling installation as final filter stage and for air distribution
- Fitting of filter elements for the separation of suspended particles such as aerosols, toxic dusts, viruses and bacteria from the supply or extract air

### Special characteristics

- Compact construction
- Easy operation
- High operational reliability

### Classification

- Variants SC, TC, and SR conform to hygiene requirements

### Nominal sizes [mm]

- 400, 500, 600, 625, 680

### Variants

- SC: Side entry circular spigot
- SC00H: Side entry circular spigot, manually adjustable shut-off damper
- SCTN0: Side entry circular spigot, shut-off damper with pneumatic actuator
- SCBR0: Side entry circular spigot, shut-off damper with electric actuator 24 – 240 V AC
- SCVFL: Side entry circular spigot, volume flow limiter
- TC: Top entry circular spigot
- SR: Side entry rectangular spigot
- SRKSR: Side entry rectangular spigot, manually adjustable shut-off damper

### Construction

- SPC: Steel, powder-coated RAL 9010, pure white
- STA: Stainless steel (only for SC, TC, SR)

### Parts and characteristics

- Pneumatic actuator: control pressure 0.6 – 1.0 bar
- Electric actuator: mains connection 24 – 240 V, 50 Hz
- Volume flow limiter: factory set reference volume flow rate, can be readjusted within a volume flow rate range of > 5 : 1

### Attachments

- ADLQ: Ceiling diffuser
- DLQ: Ceiling diffuser

- FD: Ceiling swirl diffuser
- TDF: Ceiling swirl diffuser
- FDF: Ceiling swirl diffuser
- VDW: Ceiling swirl diffuser
- DLQLF: Ceiling diffuser
- DLQL: Ceiling swirl diffuser with baffle element made of acoustic fleece
- PCD: PROCONDIF® diffuser
- AIRNAMIC: Ceiling swirl diffuser

#### Options

- D: Spigot diameter
- M: Damper blade for volume flow rate balancing
- 2: Installation subframe with 2 fixing points
- 4: Installation subframe with 4 fixing points
- T: Top suspension and measurement points
- S: Side suspension and measurement points

#### Useful additions

- Mini Pleat filter panels (MFP)
- Suitable filter elements to be ordered separately

#### Construction features

- Clamping mechanism with 2 fixing points for filter elements; 4 fixing points as an option
- Sealing integrity test facility for checking the filter function
- Pressure measurement points to monitor the differential operating pressure

#### Materials and surfaces

- Casing made of either sheet steel, powder-coated RAL 9010, pure white, or of stainless steel for variants SC, TC and SR
- Diffusers made of sheet steel, powder-coated RAL 9010, pure white (types DLQ, FD, TDF, VDW, DLQLF, DLQL), of anodised aluminium sections (type ADLQ), or of stainless steel (type FDF)
- Diffuser made of sheet steel, powder-coated RAL 9010 (pure white, matt); type PCD with internal part made of PP plastic, RAL 9010 (pure white)
- Diffuser made of high-quality ABS plastic, RAL 9010 (pure white), type AIRNAMIC

#### Standards and guidelines

- Hygiene meets the requirements of VDI 6022, VDI 3803, DIN 1946 Part 4, ÖNORM H 6021 and ÖNORM H 6020, SWKI VA 104-01 and SWKI 99-3, and EN 13779

#### Maintenance

- For constructions with shut-off damper, the filter change and other maintenance work can be carried out without disturbance of the system operation
- Diffusers with central fixing facilitate removal for filter change and decontamination

## TECHNICAL INFORMATION

Function, Specification text, Order code, Related products

---

Variants, Dimensions and weight, Product details

---

## Installation details, Basic information and nomenclature

---

### TROX UK Ltd

---



Caxton Way,  
Thetford, Norfolk, IP24 3SQ, UK  
Tel: +44 (0) 1842 754545  
Fax: +44 (0) 1842 763051

General Enquiries –  
[info@troxuk.co.uk](mailto:info@troxuk.co.uk)  
Sales & Customer Services –  
[sales@troxuk.co.uk](mailto:sales@troxuk.co.uk)  
Accounts –  
[accounts@troxuk.co.uk](mailto:accounts@troxuk.co.uk)

### Online-Services

---

- > [TROX Academy](#)

---

- > [Your contact partner](#)

---

- > [Our Office London](#)

---

- > [Our Office Thetford](#)

---

### Service-Hotlines

---

Sales:  
+44 (0)1842 754545  
[Contact](#)

Service:  
+44 (0)1842 754545  
[Contact](#)

Technical service  
+44 (0)1842 754545  
[Contact](#)